WebDT Signage Appliance SA1000/ SA2000





Key Features:

- Microsoft® Windows® XP Embedded operating system
- Intuitive, web-based remote content and device administration
- Compact size for ease in installation and mounting
- Fan or Fanless, HDD or Flashed based storage
- Optional wireless networking
- Support for numerous media formats (e.g., images, videos, Flash, URL, RSS, PowerPoint)
- Real-time or scheduled content playback
- Flexible screen layout options with multiple zones and layers
- Automatic content download recovery

The WebDT Signage Appliance by DT Research enables efficient deployment of a digital signage system. The reliable hardware together with an innovative server software suite, facilitates the creation of a unique and powerful communications medium that offers unparalleled opportunities to capture an audience's attention at key decision-making locations. When connected to a display, the WebDT Signage Appliances are ready to deliver timely, targeted communications, to the right place, at the right time.

The WebDT Signage Appliances feature powerful and high-performance processors in compact and robust packages. The WebDT Signage Appliances power displays with dynamic content while communicating with the server for continuous updates. With VGA and HDMI outputs, the network-ready WebDT Signage Appliances offer efficient and flexible deploymentsl.

WebDT Content Manager

The web-enabled WebDT Content Manager software provides central management of WebDT signage appliances as media players, and automates the design and distribution of a wide variety of multimedia file format. With the WebDT Content Manager, the message to be played is assembled, scheduled, and delivered for dynamic playback over a network of appliances using standard file formats and protocols.

Feature Highlights:

- Groups and Players
- Media Management
- Ticker
- Multiple-zones
- Preset Templates
- PlaylistsScheduling
- Uraent Casts
- System Management
- Reporting
- Auto Recovery



WebDT Device Manager

WebDT Device Manager offers comprehensive management, and provides a web browser interface fronting a database management system which supports a network of WebDT signage appliances over the LAN, WAN, or wireless networks.

The WebDT Device Manager utilizes "push and pull" technology to interact with remote appliances, allowing system administrators to inventory hardware, update applications and registry entries, shutdown/reboot/ wake-up devices, update system firmware and software, along with access to advanced logging and scheduling capabilities.

Feature Highlights:

- Client Inventory
- History and Job Manager
- Scheduling
- Group Management
- Appliance Shutdown
- WakeOnLan
- Image Management
- File Package
- BIOS Management
- Database Support

HUNDRIT	140000000000000000000000000000000000000							and a
	Device Manager							
	diam.		K (Netst) (Set H) (See H)			Section data		* Unit
	in data.							
		See.	Trange to	EAter	Sec	ines.	(Nexus)	
	100	WEIGHT !		410101	10.00	10.000363	No test for 2	
	0	100344		10.101.00.00	10.40	1010710	40.000.000.0	
	D	MODE .		46.48.1875	DOM: N	10-40106	6 10 10 2	0.00
	0	HET HAT		46.10110276	rawar.	cal-wathat	4 10:013	
	D	202364		wasten.	10.007	GIVENE	10.101.012	
	10	101364		610104	19-491	10-101108	40 100 100 2	
	12	902364		8.10.10.1	10.001	12.46716	46.100.1002	
	10	10035-0		200,200-1-00	02-487	CE-wetrings	4444	
	10	100381		418.85	12:481	10100100	400.007	
	0	10038-20		380 200 121	10+01	1010718	46 00 062	
		MEMA		調測に設	10.407	101074	#18:002	
	0	received		46.001.00	10.00	12-1010	94,961962	
		2015.8		4.00.000	10.00	-	40.003	
	. 0	38238.8		44.16.18.19	18465	10100108	4884	
	R	MORE		****	10.00		-	
				mitte propert and	angen		A T Apres	

Comparison Chart

Products	Item	SA1000	SA2000		
	Processor	1.5GHz x86 processor	AMD Sempron™ 1.6GHz/ 2GHz, or AMD Turion™ 2.1GHz Dual-Core processor		
	RAM	1GB (DDR II SODIMM x 1)	1GB or 2GB (DDR II SODIMM x 1)		
	Storage	4GB, 8GB, or 16GB Flash	4GB, 8GB or 16GB Flash, or 120GB HDD		
	Display	Up to 1920 x1080	Up to 1920 x 1080		
System	Operating System	Microsoff® Windows® XP Embedded			
	Wireless Connection	10/100Mb BaseT LAN/ WiFi 802.11 a/b/g			
		DVI-I (1)	VGA (1)		
		Audio jack (3)	HDMI (1)		
		USB port (4)	Audio jack (3)		
		RJ45 connector for Ethernet (1)	USB port (2)		
		DC-in jack (1)	RJ45 connector for Ethernet (1)		
			DC-in jack (1)		
	I/O Ports	Optional:	S-Video input (1)		
		WiFi Dipole antenna (1)	Composite video-in (1)		
			RS232 COM port (1)		
			Optional:		
			WiFi Dipole antenna (1)		
Machania	Dimension (H x W x D)	1.7" x 5.5" x 5.1"	2" x 5.5" x 6.5"		
Mechanical	Weight	1.2 lbs/ 544g	2.97 lbs/ 1344g		
Environmental	Regulatory	FCC Class B, CE, C-tick, RoHS compliant			
	Operating Temperature	0° – 40°C			
	Humidity	0% – 90% non-condensing			

* Specifications subject to change without notice.

Applications:

The WebDT Signage Appliance is ideal for the following applications:

Retail

- Transportation
- Hospitality
- Casino/ Entertainment
 Healthcare
- Government
- Kiosk
- - Finance







DT Research, Inc.

2000 Concourse Drive, San Jose, CA 95131 http://www.dtresearch.com I http://signage.dtri.com Copyright © 2008-2009, DT Research, Inc. All Rights Reserved. DT Research and WebDT are registered trademarks of DT Research, Inc.